

Descriptions:

The IRPT908 (Slot Optical Switch) is a gallium arsenide infrared emitting diode which is coupled with a silicon photo transistor in a plastic housing. The packaging system is designed to optimize the mechanical resolution, coupling efficiency, and insulates ambient light. The slot in the housing provides a means of interrupting the signal with printer, scanner, copier, or other opaque material, switching the output from an "ON" to "OFF" state.


Features:

- Wide gap between light emitter and detector (5.0mm)
- High sensing accuracy
- PWB mounting type package

Applications:

- Copier
- Printer
- Facsimile
- Ticket vending machine
- Opto-electronic switch

Package Dimensions :



Absolute Maximum Ratings (Ta=25°C)

| Parameter | | Symbol | Ratings | Unit |
|---|--|------------------|---------|------|
| Input | Power Dissipation at(or below) 25°C Free Air Temperature | Pd | 75 | mW |
| | Reverse Voltage | V _R | 5 | V |
| | Forward Current | I _F | 50 | mA |
| | Peak Forward Current Pulse width ≤ 100μs, Duty cycle=1% | I _{FP} | 1 | A |
| Output | Collector Power Dissipation | P _C | 75 | mW |
| | Collector Current | I _C | 20 | mA |
| | Collector-Emitter Voltage | V _{CEO} | 30 | V |
| | Emitter-Collector Voltage | V _{ECO} | 5 | V |
| Operating Temperature | | Topr | -25~+85 | °C |
| Storage Temperature | | Tstg | -40~+85 | °C |
| Lead Soldering Temperature (1/16 inch from body for 5 seconds) | | Tsol | 260 | °C |

Electro-Optical Characteristics (Ta=25°C)

| Parameter | | Symbol | Min. | Typ. | Max. | Unit | Condition |
|-------------------------|------------------------|----------------------|------|------|------|------|--|
| Input | Forward Voltage | V _F | - | 1.2 | 1.5 | V | I _F =20mA |
| | Reverse Current | I _R | - | - | 10 | μA | V _R =5V |
| | Peak Wavelength | λ _P | - | 940 | - | nm | I _F =20mA |
| Output | Collector Dark Current | I _{CEO} | - | - | 100 | nA | V _{CE} =20V Ee=0mW/ |
| Transfer Characteristic | C-E Saturation Voltage | V _{CE(sat)} | - | - | 0.4 | V | I _C =0.5mA Ee=10mW/cm ² |
| | Collector Current | I _{C(ON)} | 0.5 | - | - | mA | V _{CE} =5V I _F =20mA |
| | Rise time | t _r | - | 1 | 5- | μsec | V _{CE} =5V |
| | Fall time | t _f | - | 1 | 5- | μsec | I _C =1mA R _L =1KΩ |

Typical Characteristics For IR

Fig. 1 Forward Current vs. Ambient Temperature




Fig. 2 Spectral Distribution




Fig. 3 Peak Emission Wavelength vs. Ambient Temperature




Fig. 4 Forward Current vs. Forward Voltage




Fig. 5 Forward Voltage vs. Ambient Temperature











Fig. 6 Relative Radiant Intensity vs. Angular Displacement



Typical Characteristics For PT



Typical Characteristics For ITR



Reliability test item and condition

The reliability of products shall be satisfied with item listed

below: Confidence level :90%

LTPD:10%

| Parameter | Purpose & Condition | Failure Judgement Criteria | Samples(n) Defective(c) |
|--------------------------|--|---|----------------------------|
| Temperature Cycle | Evaluates product's ability to withstand exposure to high temperature, low temperature, and temperature variation between two limit temperature. Standard test Condition: $85^{\circ}\text{C} \sim 25^{\circ}\text{C} \sim -55^{\circ}\text{C} \sim 25^{\circ}\text{C}$ <div style="text-align: center;"> $\downarrow \quad \downarrow \quad \downarrow \quad \downarrow$ 30min 5min 30min 5min 50 cycle </div> | $I_R \geq U \times 2$ $I_{c(on)} \leq L \times 0.8$ $V_F \geq U \times 1.2$ U : Upper specificatio limit L : Lower specificatio limit | n =22 , c=0 |
| Thermal Shock | Evaluates product's ability to withstand rapid temperature change Standard test Condition: $85^{\circ}\text{C} \sim -55^{\circ}\text{C}$ 5 min 5 min 50cycle | | n =22 , c=0 |
| High Temperature Storage | Evaluates product's ability to withstand prolonged storage at high temperature Standard test Condition: Temperature : 100 $^{\circ}\text{C}$ Time : 1000hrs | | n =22 , c=0 |
| Low Temperature Storage | Evaluates product's ability to withstand prolonged storage at low temperature Standard test Condition: Temperature : -55 $^{\circ}\text{C}$ Time : 1000hrs | | n =22 , c=0 |

| Parameter | Purpose & Condition | Failure Judgement Criteria | Samples(n) Defective(c) |
|-----------------------------------|--|--|----------------------------|
| Operating Life Test | Evaluates product's endurance to prolonged electrical or temperature stresses. Standard test Condition: $V_{CE}=5V$ $I_F=20mA$ Time : 1000hrs | $I_R \geq U \times 2$ $I_{c(on)} \leq L \times 0.8$ $V_F \geq U \times 1.2$ U : Upper specification limit | n =22 , c=0 |
| High Temperature High Humidity | Evaluates product's ability to withstand prolonged storage at high temperature and high humidity. Standard test Condition: Temperature: 85°C Relative humidity:85% Time : 1000hrs | L : Lower specification limit | n =22 , c=0 |
| Soldering Heat | Evaluates product's ability to withstand soldering heat Standard test conditions Solder temperature : 260±5°C Solder time : 10 seconds | | n =22 , c=0 |

Supplement

Parts

Chip

| Type | Material | Peak Wavelength |
|------|----------|-----------------|
| IR | GaAs | 940 nm |
| PT | Silicon | 860 nm |

Material

| Type | Lead frame | Wire | Part Package | Holder |
|----------|------------|------|--------------|--------|
| Material | SPCC | Gold | Epoxy | NYLON |

Notes :

- 1.All dimensions are in millimeter.
- 2.General Tolerance:± 0.2mm
- 3.Leadspacingis measured where the lead emerge from the package.
- 4.Above specification may be changed without notice. will reserve authority on material change for above specification.
- 5.When using this product , please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.